



SILKFLEX POLYMERS SDN BHD (545022-T)

No.98, (Lot 9115), Jalan Tengah KS10 Telok Gong,
42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia
Tel: +6-03-31341702 / 1703 / 1260 Fax: +6-03-3134 1670
Email : silkflexpolymers@hotmail.com
Website : www.silkflex.com.my
GST Reg. No.: 000094011392

Fluorescent Pigment Green

PRODUCT INTRODUCTION

Chemical Composition	Water-based Basic Yellow 40 and Pigment Green 7, pigment mixture.	
Uses	As a colorant for Textile Printing Paste.	
CAS No	12221-86-2	1328-53-6
CI No	Basic Yellow 40	74260

PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity at 27 (°C)	1.05 – 1.15
Solid Content (%)	40 – 45%

Chemical Property	Performance
Light Fastness	Good
Heat Resistance	160 °C
Acid Resistance	Excellent
Alkali Resistance	Excellent

PRODUCT PREPARATION

Mixing Ratio	Textile Printing Paste	100 parts by weight
	Fluorescent Pigment Green	0.1– 10.0 parts by weight

SHELF LIFE

12 months from date of manufacture. The date refers to product held in its original closed packaging.

STORAGE

Keep containers in a cool ventilated environment, temperature between 20 °C to 30 °C. With partial use, close container tight and use the remainder as soon as possible.