



## SILKFLEX POLYMERS SDN BHD (545022-T)

No.98, (Lot 9115), Jalan Tengah KS10 Telok Gong,  
42000 Pelabuhan Klang, Selangor Darul Ehsan, Malaysia  
Tel: +6-03-31341702 / 1703 / 1260 Fax: +6-03-3134 1670  
Email : silkflexpolymers@hotmail.com  
Website : www.silkflex.com.my  
GST Reg. No.: 000094011392

### Pigment Green

#### **PRODUCT INTRODUCTION**

Chemical Composition	Water based Pthaloyanine Pigment Paste.
Uses	As a colorant for Silkflex Textile Printing Paste.
CAS No	1328-53-6
CI No	74260

#### **PHYSICAL AND CHEMICAL PROPERTIES**

Specific Gravity at 27 (°C)	1.30 – 1.50
Pigment Content (%)	47 ± 1

Chemical Property	Performance
Light Fastness	Excellent
Weather Fastness	Excellent
Heat Resistance	200 °C
Acid Resistance	Excellent
Alkali Resistance	Excellent

#### **PRODUCT PREPARATION**

Mixing Ratio	Silkflex Textile Printing Paste	100 parts by weight
	Silkflex Pigment Green	0.1– 10.0 parts by weight

#### **SHELF LIFE**

12 months from date of manufacture. The date refers to product held in its original closed packaging.

#### **STORAGE**

Keep containers in a cool ventilated environment, temperature between 20 °C to 30 °C. With partial use, close container tight and use the remainder as soon as possible.